Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation



# 026982 - ANTIGOTERAS MEMBRANA POLIURETANO Blanco

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier:

026982 - ANTIGOTERAS MEMBRANA POLIURETANO Blanco

## Other means of identification:

Non-applicable

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Waterproofing agents for terraces and facades

Uses advised against: All uses not specified in this section or in section 7.3

## 1.3 Details of the supplier of the safety data sheet:

Productos JAFEP, S.L. Carretera de Barrax, s/n 02630 La Roda - Albacete - Spain Phone: +34 967 44 05 96 - Fax: +34 967 44 26 12 jafep@jafep.com www.jafep.com

**1.4 Emergency telephone number:** +34 967 44 05 96 (9:00 - 14:00 ; 16:00-20:00 )

# SECTION 2: HAZARDS IDENTIFICATION \*\*

The product has been classified in accordance with the information contained in the suppliers' SDS and the additional information from tests carried out by said suppliers

# 2.1 Classification of the substance or mixture:

#### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

#### 2.2 Label elements:

## CLP Regulation (EC) No 1272/2008:

# Hazard statements:

Harmful to aquatic life with long lasting effects.

### **Precautionary statements:** Experts

If medical advice is needed, have product container or label at hand.

Keep out of reach of children. Avoid release to the environment.

Dispose of contents/container according to the separated collection system used in your municipality.

#### Supplementary information:

Contains 1,2-benzisothiazol-3(2H)-one, octhilinone (ISO), reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria Endocrine-disrupting properties: The product fails to meet the criteria.

\*\* Changes with regards to the previous version

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

## 3.1 Substance:

Non-applicable

3.2 Mixture: Chemical description: Miscellaneous products Components:

\*\* Changes with regards to the previous version



#### Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# 026982 - ANTIGOTERAS MEMBRANA POLIURETANO Blanco

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\* (continued)

# In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification	Chemical name/Classification	Concentration
CAS:	330-54-1	diuron (ISO) <sup>(1)</sup> ATP ATP01	
	206-354-4 006-015-00-9 01-2119517622-45- XXXX	Regulation 1272/2008       Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Carc. 2:         H351; STOT RE 2: H373 - Warning	<0,09 %
CAS:	26530-20-1	octhilinone (ISO) <sup>(1)</sup> ATP ATP15	5
	247-761-7 613-112-00-5 01-2120768921-45- XXXX	Regulation 1272/2008         Acute Tox. 2: H330; Acute Tox. 3: H301+H311; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1: H314; Skin Sens. 1A: H317; EUH071 - Danger	<0,09 %
CAS:	2634-33-5	1,2-benzisothiazol-3(2H)-one <sup>(1)</sup> ATP CLP00	
	220-120-9 613-088-00-6 01-2120761540-60- XXXX	Regulation 1272/2008 Acute Tox. 4: H302; Aquatic Acute 1: H400; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	<0,09 %
CAS:	111-76-2	2-butoxyethanol <sup>(2)</sup> ATP ATP15	
	203-905-0 603-014-00-0 01-2119475108-36- XXXX	Regulation 1272/2008 Acute Tox. 4: H302+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	<0,09 %
CAS: EC:	55965-84-9 Non-applicable	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- ATP ATP13 one (3:1) <sup>(1)</sup>	3
	613-167-00-5 Non-applicable	Regulation 1272/2008         Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger	<0,09 %
CAS:	50-00-0	Formaldehyde (2) ATP ATPOE	
EC: Index: REACH:	200-001-8 605-001-00-5 01-2119488953-20- XXXX	Acute Tox. 3: H301+H311+H331; Carc. 1B: H350; Muta. 2: H341; Skin Corr. 1B:           H314; Skin Sens. 1: H317 - Danger	<0,09 %
CAS: EC:	55965-84-9 Non-applicable	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- ATP ATP13 one (3:1) <sup>(1)</sup>	3
	613-167-00-5 Non-applicable	Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger	<0,09 %

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 (2) Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

#### **Other information:**

	Identification			M-factor
diuron (ISO)			Acute	10
CAS: 330-54-1	EC: 206-354-4		Chronic	10
octhilinone (ISO)			Acute	100
CAS: 26530-20-1	EC: 247-761-7		Chronic	100
reaction mass of 5-cl	loro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol	-3-one (3:1)	Acute	100
CAS: 55965-84-9	EC: Non-applicable		Chronic	100
reaction mass of 5-cl	loro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol	-3-one (3:1)	Acute	100
CAS: 55965-84-9	EC: Non-applicable		Chronic	100
	Identification	Spec	ific concentr	ation limit

Identification	Specific concentration limit
octhilinone (ISO) CAS: 26530-20-1 EC: 247-761-7	% (w/w) >=0,0015: Skin Sens. 1A - H317
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	% (w/w) >=0,05: Skin Sens. 1 - H317
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H- isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable	% (w/w) >=0,6: Skin Corr. 1C - H314 0,06<= % (w/w) <0,6: Skin Irrit. 2 - H315 % (w/w) >=0,6: Eye Dam. 1 - H318 0,06<= % (w/w) <0,6: Eye Irrit. 2 - H319 % (w/w) >=0,0015: Skin Sens. 1A - H317

\*\* Changes with regards to the previous version

Pinturnas Jafep Experts in decoration"

# legislation 026982 - ANTIGOTERAS MEMBRANA POLIURETANO Blanco

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\* (continued)

Identification	Specific concentration limit
Formaldehyde CAS: 50-00-0 EC: 200-001-8	% (w/w) >=25: Skin Corr. 1B - H314 5<= % (w/w) <25: Skin Irrit. 2 - H315 % (w/w) >=25: Eye Dam. 1 - H318 5<= % (w/w) <25: Eye Irrit. 2 - H319 % (w/w) >=0,2: Skin Sens. 1 - H317 % (w/w) >=5: STOT SE 3 - H335
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H- isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable	% (w/w) >=0,6: Skin Corr. 1C - H314 0,06<= % (w/w) <0,6: Skin Irrit. 2 - H315 % (w/w) >=0,6: Eye Dam. 1 - H318 0,06<= % (w/w) <0,6: Eye Irrit. 2 - H319 % (w/w) >=0,0015: Skin Sens. 1A - H317

CAS: 26530-20-1 (2-octyl-2H-isothiazol-3-one), the total content is indicated, free / total percentage10%;

CAS: 330-54-1 (diuron), the total content is indicated, percentage free / total 10%.

Classification calculation based on supplier testing information:

Only the content of free OIT is toxicologically relevant and must be taken into account for the classification of the preparation in relation to danger for the environment, irritation to skin and eyes, sensitization.

Only the content of free Diuron is toxicologically relevant and must be taken into account for the classification of the preparation in relation to the danger for the environment.

\*\* Changes with regards to the previous version

# SECTION 4: FIRST AID MEASURES

# 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

# By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

#### By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

# By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

# 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

#### Non-applicable

## SECTION 5: FIREFIGHTING MEASURES

## 5.1 Extinguishing media:

#### Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

#### Unsuitable extinguishing media:

Non-applicable

## 5.2 Special hazards arising from the substance or mixture:

legislation



# 026982 - ANTIGOTERAS MEMBRANA POLIURETANO Blanco

## SECTION 5: FIREFIGHTING MEASURES (continued)

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

#### For emergency responders:

See section 8.

6.3

#### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

Methods and material for containment and cleaning up:

#### It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

## 6.4 Reference to other sections:

See sections 8 and 13.

# SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

# 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

B.- General conditions for storage



legislation

## 026982 - ANTIGOTERAS MEMBRANA POLIURETANO Blanco

# SECTION 7: HANDLING AND STORAGE (continued)

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

	Identification	Occupa	ational exposure lir	nits
2-butoxyethanol		IOELV (8h)	20 ppm	98 mg/m <sup>3</sup>
CAS: 111-76-2	EC: 203-905-0	IOELV (STEL)	50 ppm	246 mg/m <sup>3</sup>
Formaldehyde		IOELV (8h)	0,3 ppm	0,37 mg/m <sup>3</sup>
CAS: 50-00-0	EC: 200-001-8	IOELV (STEL)	0,6 ppm	0,74 mg/m <sup>3</sup>

## DNEL (Workers):

		Short	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
diuron (ISO)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 330-54-1	Dermal	Non-applicable	Non-applicable	5,79 mg/kg	Non-applicable
EC: 206-354-4	Inhalation	Non-applicable	Non-applicable	0,17 mg/m <sup>3</sup>	Non-applicable
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,966 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	6,81 mg/m <sup>3</sup>	Non-applicable
2-butoxyethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	125 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	1091 mg/m <sup>3</sup>	246 mg/m <sup>3</sup>	98 mg/m <sup>3</sup>	Non-applicable
Formaldehyde	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 50-00-0	Dermal	Non-applicable	Non-applicable	240 mg/kg	Non-applicable
EC: 200-001-8	Inhalation	Non-applicable	0,75 mg/m <sup>3</sup>	9 mg/m <sup>3</sup>	0,375 mg/m <sup>3</sup>

#### **DNEL (General population):**

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,345 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	1,2 mg/m <sup>3</sup>	Non-applicable
2-butoxyethanol	Oral	Non-applicable	Non-applicable	6,3 mg/kg	Non-applicable
CAS: 111-76-2	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
EC: 203-905-0	Inhalation	426 mg/m <sup>3</sup>	147 mg/m <sup>3</sup>	59 mg/m <sup>3</sup>	Non-applicable
Formaldehyde	Oral	Non-applicable	Non-applicable	4,1 mg/kg	Non-applicable
CAS: 50-00-0	Dermal	Non-applicable	Non-applicable	102 mg/kg	Non-applicable
EC: 200-001-8	Inhalation	Non-applicable	Non-applicable	3,2 mg/m <sup>3</sup>	0,1 mg/m <sup>3</sup>

PNEC:

Identification				
diuron (ISO)	STP	58 mg/L	Fresh water	0,00032 mg/L
CAS: 330-54-1	Soil	0,012 mg/kg	Marine water	0,000032 mg/L
EC: 206-354-4	Intermittent	0,00022 mg/L	Sediment (Fresh water)	0,052 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,005 mg/kg



# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
octhilinone (ISO)	STP	Non-applicable	Fresh water	0,0022 mg/L
CAS: 26530-20-1	Soil	0,0082 mg/kg	Marine water	0,00022 mg/L
EC: 247-761-7	Intermittent	0,00122 mg/L	Sediment (Fresh water)	0,0475 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00475 mg/kg
1,2-benzisothiazol-3(2H)-one	STP	1,03 mg/L	Fresh water	0,00403 mg/L
CAS: 2634-33-5	Soil	3 mg/kg	Marine water	0,000403 mg/L
EC: 220-120-9	Intermittent	0,0011 mg/L	Sediment (Fresh water)	0,0499 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00499 mg/kg
2-butoxyethanol	STP	463 mg/L	Fresh water	8,8 mg/L
CAS: 111-76-2	Soil	2,33 mg/kg	Marine water	0,88 mg/L
EC: 203-905-0	Intermittent	26,4 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	3,46 mg/kg
Formaldehyde	STP	0,19 mg/L	Fresh water	0,44 mg/L
CAS: 50-00-0	Soil	0,2 mg/kg	Marine water	0,44 mg/L
EC: 200-001-8	Intermittent	4,44 mg/L	Sediment (Fresh water)	2,3 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	2,3 mg/kg

## 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

#### C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		decoration® EN 420:2004+A1:2010	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

## D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
Body protection				
Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product fo professional/industrial users CE III is recommended, in accordance with the regulation in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CATI	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulation

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



# 026982 - ANTIGOTERAS MEMBRANA POLIURETANO Blanco

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:201
Environmental exposure cont	rols:		
-	y legislation for the protection of		ecommended to avoid environmenta .1.D
With regard to Directive 2010/75/	FIL this product has the following	a characteristics.	
V.O.C. (Supply):	0,06 % weight		
V.O.C. density at 20 °C:	0,79 kg/m <sup>3</sup> (0,79 g/L)		
Average carbon number:	4,54		
-	118,65 q/mol		
Average molecular weight:	1 5.	, uso has the following	- charactorictics
With regard to Directive 2004/42/		use has the following	
V.O.C. density at 20 °C:	0,79 kg/m <sup>3</sup> (0,79 g/L)		
EU limit for the product (Cat.			
Components:	Non-applicable		
ION 9: PHYSICAL AND CHEM	ICAL PROPERTIES		
Information on basic physical	and chemical properties:		
For complete information see the	Pu		
Appearance:			
Physical state at 20 °C:	Liquid		
Appearance:	Viscous		
Appearance: Colour:	Viscous		
Colour:	Experts 🔲 White	oration® stic	
Colour: Odour:	Experts White Characteri	stic	
Colour: Odour: Odour threshold:	Experts 🔲 White	stic	
Colour: Odour: Odour threshold: Volatility:	Experts White Characteri Non-applic	stic	
Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmospheric press	Experts  White    Characteri    Non-applic    sure:    102 °C	stic	
Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmospheric press Vapour pressure at 20 °C:	Experts White Characteri Non-applic sure: 102 °C 2355 Pa	stic cable *	
Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C:	Experts White Characteri Non-applic sure: 102 °C 2355 Pa 12374,65	stic cable * Pa (12,37 kPa)	
Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C:	Experts White Characteri Non-applic sure: 102 °C 2355 Pa	stic cable * Pa (12,37 kPa)	
Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: <b>Product description:</b>	Experts White Characteri Non-applic sure: 102 °C 2355 Pa 12374,65 Non-applic	stic cable * Pa (12,37 kPa) cable *	
Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: <b>Product description:</b> Density at 20 °C:	Experts White Characteri Non-applic sure: 102 °C 2355 Pa 12374,65 Non-applic ≈1300,6 k	stic cable * Pa (12,37 kPa) cable *	
Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: <b>Product description:</b> Density at 20 °C: Relative density at 20 °C:	Experts White Characteri Non-applic sure: 102 °C 2355 Pa 12374,65 Non-applic ≈1300,6 k ≈1,301	stic cable * Pa (12,37 kPa) cable * cg/m <sup>3</sup>	
Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: <b>Product description:</b> Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C:	Experts White Characteri Non-applic sure: 102 °C 2355 Pa 12374,65 Non-applic ≈1300,6 k ≈1,301 Non-applic	stic cable * Pa (12,37 kPa) cable * cg/m <sup>3</sup> cable *	
Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: <b>Product description:</b> Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C:	Experts White Characteri Non-applic sure: 102 °C 2355 Pa 12374,65 Non-applic ≈1300,6 k ≈1,301 Non-applic Non-applic	stic cable * Pa (12,37 kPa) cable * cg/m <sup>3</sup> cable *	
Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: <b>Product description:</b> Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C:	Experts White Characteri Non-applic sure: 102 °C 2355 Pa 12374,65 Non-applic ≈1300,6 k ≈1,301 Non-applic Non-applic Non-applic Non-applic	stic cable * Pa (12,37 kPa) cable * cg/m <sup>3</sup> cable * cable * cable *	
Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration:	Experts White Characteri Non-applic sure: 102 °C 2355 Pa 12374,65 Non-applic ≈1300,6 k ≈1,301 Non-applic >20,5 mm Non-applic	stic cable * Pa (12,37 kPa) cable * cg/m <sup>3</sup> cable * cable * cable *	
Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Concentration: pH:	Experts White Characteri Non-applic sure: 102 °C 2355 Pa 12374,65 Non-applic ≈1300,6 k ≈1,301 Non-applic Non-applic >20,5 mm Non-applic 8 - 10	stic cable * Pa (12,37 kPa) cable * cable * cable * cable * cable * cable *	
Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 50 °C: Evaporation rate at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Cincentration: Concentration:	Experts White Characteri Non-applic sure: 102 °C 2355 Pa 12374,65 Non-applic ≈1300,6 k ≈1,301 Non-applic >20,5 mm Non-applic	stic cable * Pa (12,37 kPa) cable * cable * cable * cable * cable * cable *	
Colour: Odour: Odour threshold: <b>Volatility:</b> Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: <b>Product description:</b> Density at 20 °C: Relative density at 20 °C: Concentration: pH:	Experts White Characteri Non-applic sure: 102 °C 2355 Pa 12374,65 Non-applic ≈1300,6 k ≈1,301 Non-applic >20,5 mm Non-applic 8 - 10 Non-applic	stic cable * Pa (12,37 kPa) cable * cable * cable * cable * cable * cable *	
Colour: Odour: Odour threshold: Volatility: Boiling point at atmospheric press Vapour pressure at 20 °C: Vapour pressure at 20 °C: Evaporation rate at 20 °C: Evaporation rate at 20 °C: Product description: Density at 20 °C: Relative density at 20 °C: Dynamic viscosity at 20 °C: Kinematic viscosity at 20 °C: Kinematic viscosity at 40 °C: Concentration: pH: Vapour density at 20 °C:	Experts White Characteri Non-applic sure: 102 °C 2355 Pa 12374,65 Non-applic ≈1300,6 k ≈1,301 Non-applic >20,5 mm Non-applic 8 - 10 Non-applic	stic cable * Pa (12,37 kPa) cable * cg/m <sup>3</sup> cable * cable * cable * cable * cable *	

- CONTINUED ON NEXT PAGE -

Version: 2 (Replaced 1)

Revised: 24/02/2022

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



# 026982 - ANTIGOTERAS MEMBRANA POLIURETANO Blanco

SECT	TION 9: PHYSICAL AND CHEMICAL PROPERTIE	S (continued)	
	Decomposition temperature:	Non-applicable *	
	Melting point/freezing point:	Non-applicable *	
	Flammability:		
	Flash Point:	Non Flammable (>60 °C)	
	Flammability (solid, gas):	Non-applicable *	
	Autoignition temperature:	238 °C	
	Lower flammability limit:	Non-applicable *	
	Upper flammability limit:	Non-applicable *	
	Particle characteristics:		
	Median equivalent diameter:	Non-applicable	
9.2	Other information:		
	Information with regard to physical hazard clas	sses:	
	Explosive properties:	Non-applicable *	
	Oxidising properties:	Non-applicable *	
	Corrosive to metals:	Non-applicable *	
	Heat of combustion:	Non-applicable *	
	Aerosols-total percentage (by mass) of flammable components:	Non-applicable *	
	Other safety characteristics:		
	Surface tension at 20 °C:	Non-applicable *	
	Refraction index:	Non-applicable *	
	*Not relevant due to the nature of the product, not providing info	prmation property of its hazards.	
		ΠΡΝ	

# SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

#### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### **10.4** Conditions to avoid:

Applicable for handling and storage at room temperature:

	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
10.5	Incompatible materials	:			

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

# **10.6** Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

# SECTION 11: TOXICOLOGICAL INFORMATION \*\*

# **11.1** Information on hazard classes as defined in Regulation (EC) No 1272/2008:

\*\* Changes with regards to the previous version

legislation



## 026982 - ANTIGOTERAS MEMBRANA POLIURETANO Blanco

# SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

# Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

- B- Inhalation (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
  - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met. as dangerous with carcinogenic effects. For more information see section 3.

IARC: Distillates (petroleum), hydrotreated light paraffinic (3); Distillates (petroleum), hydrotreated light naphthenic (3); 2butoxyethanol (3); Titanium dioxide (2B); Talc (3); Formaldehyde (1)

- Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.

- Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

## Other information:

Not skin sensitizing based on the results of similar mixtures tested in accordance with the bridging principles described in Article 9 (4) of the CLP Regulation; OECD 429 LLNA (mouse): not skin sensitiser- S4565; S4568 Specific toxicology information on the substances:

\*\* Changes with regards to the previous version



# SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)

Identification	A	cute toxicity	Genus
diuron (ISO)	LD50 oral	1017 mg/kg	Rat
CAS: 330-54-1	LD50 dermal	Non-applicable	
EC: 206-354-4	LC50 inhalation	Non-applicable	
octhilinone (ISO)	LD50 oral	125 mg/kg	
CAS: 26530-20-1	LD50 dermal	311 mg/kg	
EC: 247-761-7	LC50 inhalation	Non-applicable	
1,2-benzisothiazol-3(2H)-one	LD50 oral	500 mg/kg	Rat
CAS: 2634-33-5	LD50 dermal	Non-applicable	
EC: 220-120-9	LC50 inhalation	Non-applicable	
2-butoxyethanol	LD50 oral	1200 mg/kg	Rat
CAS: 111-76-2	LD50 dermal	3000 mg/kg	Rabbit
EC: 203-905-0	LC50 inhalation	Non-applicable	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LD50 oral	64 mg/kg	Rat
CAS: 55965-84-9	LD50 dermal	87,12 mg/kg	Rabbit
EC: Non-applicable	LC50 inhalation	0,33 mg/L (4 h)	Rat
Formaldehyde	LD50 oral	>5000 mg/kg	Rat
CAS: 50-00-0	LD50 dermal	>5000 mg/kg	Rabbit
EC: 200-001-8	LC50 inhalation	1,1 mg/L (4 h)	Rat
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LD50 oral	64 mg/kg	Rat
CAS: 55965-84-9	LD50 dermal	87,12 mg/kg	Rabbit
EC: Non-applicable	LC50 inhalation	0,33 mg/L (4 h)	Rat

# **11.2 Information on other hazards:**

#### **Endocrine disrupting properties**

Endocrine-disrupting properties: The product fails to meet the criteria.

# **Other information**

Non-applicable

\*\* Changes with regards to the previous version

# SECTION 12: ECOLOGICAL INFORMATION \*\*

The experimental information related to the eco-toxicological properties of the product itself is not available

- CONTINUED ON NEXT PAGE -

# 12.1 Toxicity:

\*\* Changes with regards to the previous version



# SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)

Identification		Concentration	Species	Genu
diuron (ISO)	LC50	6,6 mg/L (96 h)	Leuciscus idus	Fish
CAS: 330-54-1	EC50	1,4 mg/L (48 h)	Daphnia magna	Crusta
EC: 206-354-4	EC50	0,022 mg/L (96 h)	Scenedesmus subspicatus	Alga
octhilinone (ISO)	LC50	0,036 mg/L (96 h)	Oncorhynchus mykiss	Fisł
CAS: 26530-20-1	EC50	0,42 mg/L (48 h)	Daphnia magna	Crusta
EC: 247-761-7	EC50	0,084 mg/L (72 h)	Desmodesmus subspicatus	Alga
1,2-benzisothiazol-3(2H)-one	LC50	>0.1 - 1 (96 h)		Fish
CAS: 2634-33-5	EC50	>0.1 - 1 (48 h)		Crusta
EC: 220-120-9	EC50	>0.1 - 1 (72 h)		Alga
2-butoxyethanol	LC50	1490 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 111-76-2	EC50	1815 mg/L (48 h)	Daphnia magna	Crusta
EC: 203-905-0	EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	Alga
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2- methyl-2H-isothiazol-3-one (3:1)	LC50	>0.1 - 1 (96 h)		Fisł
CAS: 55965-84-9	EC50	>0.1 - 1 (48 h)		Crusta
EC: Non-applicable	EC50	>0.1 - 1 (72 h)		Alga
Formaldehyde	LC50	100 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 50-00-0	EC50	42 mg/L (24 h)	Daphnia magna	Crusta
EC: 200-001-8	EC50	Non-applicable		
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2- methyl-2H-isothiazol-3-one (3:1)	LC50	0,28 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 55965-84-9	EC50	0,16 mg/L (48 h)	Daphnia magna	Crustad
EC: Non-applicable	EC50	0,018 mg/L (72 h)	Selenastrum capricornutum	Alga
Chronic toxicity:				
Identification		Concentration	Species	Genu
diuron (ISO)	NOEC	0,001 mg/L	Danio rerio	Fisl
CAS: 330-54-1 EC: 206-354-4	NOEC	0,56 mg/L	Daphnia magna	Crusta
2-butoxyethanol Experts	NOEC	100 mg/L	Danio rerio	Fish
CAS: 111-76-2 EC: 203-905-0	NOEC	100 mg/L	Daphnia magna	Crusta
Formaldehyde	NOEC	Non-applicable		
CAS: 50-00-0 EC: 200-001-8	NOEC	6,4 mg/L	Daphnia magna	Crustad

\*\* Changes with regards to the previous version



# SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)

Identification	De	Degradability		egradability
diuron (ISO)	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 330-54-1	COD	Non-applicable	Period	28 days
EC: 206-354-4	BOD5/COD	Non-applicable	% Biodegradable	0 %
1,2-benzisothiazol-3(2H)-one	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 2634-33-5	COD	Non-applicable	Period	28 days
EC: 220-120-9	BOD5/COD	Non-applicable	% Biodegradable	0 %
2-butoxyethanol	BOD5	0,71 g O2/g	Concentration	100 mg/L
CAS: 111-76-2	COD	2,2 g O2/g	Period	14 days
EC: 203-905-0	BOD5/COD	0,32	% Biodegradable	96 %
Formaldehyde	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 50-00-0	COD	Non-applicable	Period	14 days
EC: 200-001-8	BOD5/COD	Non-applicable	% Biodegradable	92 %

# **12.3** Bioaccumulative potential:

Identification		Bi	Bioaccumulation potential		
diuron (ISO)		BCF	64		
CAS: 330-54-1		Pow Log	2.68		
EC: 206-354-4		Potential	Moderate		
1,2-benzisothiazol-3(2H)-one		BCF	2		
CAS: 2634-33-5		Pow Log	1.45		
EC: 220-120-9		Potential	Low		
2-butoxyethanol		BCF	3		
CAS: 111-76-2		Pow Log	0.83		
EC: 203-905-0	Pintunas.	Potential	Low		
Formaldehyde	R	BCF	3		
CAS: 50-00-0		Pow Log	0.35		
EC: 200-001-8		Potential	Low		

# 12.4 Mobility in soil:

Identification	Identification Absorption/desorption		Volatility	
2-butoxyethanol	Кос	8	Henry	1,621E-1 Pa·m <sup>3</sup> /mol
CAS: 111-76-2	Conclusion	Very High	Dry soil	No
EC: 203-905-0	Surface tension	2,729E-2 N/m (25 °C)	Moist soil	Yes
Formaldehyde	Кос	Non-applicable	Henry	Non-applicable
CAS: 50-00-0	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-001-8	Surface tension	1,416E-2 N/m (25 °C)	Moist soil	Non-applicable

\*\* Changes with regards to the previous version

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



# 026982 - ANTIGOTERAS MEMBRANA POLIURETANO Blanco

# SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)

#### 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

- **12.6 Endocrine disrupting properties:** Endocrine-disrupting properties: The product fails to meet the criteria.
- 12.7 Other adverse effects:

Not described

\*\* Changes with regards to the previous version



# SECTION 13: DISPOSAL CONSIDERATIONS

# **13.1** Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

## Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

#### **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

## SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

# SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

legislation



# 026982 - ANTIGOTERAS MEMBRANA POLIURETANO Blanco

# SECTION 15: REGULATORY INFORMATION (continued)

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 1,2benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione, (ethylenedioxy)dimethanol, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), diuron (ISO), octhilinone (ISO), 2methylisothiazol-3(2H)-one, 1,2-benzisothiazol-3(2H)-one.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: diuron (ISO) (Product-type 7, 10); octhilinone (ISO) (Product-type 6, 7, 8, 9, 10, 11, 13); 1,2-benzisothiazol-3(2H)-one (Product-type 2, 6, 9, 11, 12, 13); reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one (3:1) (Product-type 2, 4, 6, 11, 12, 13); Formaldehyde (Product-type 2, 3, 22); reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (Product-type 2, 4, 6, 11, 12, 13); REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

#### Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used in:

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### **Other legislation:**

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

# SECTION 16: OTHER INFORMATION \*\*

#### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

#### **Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:** COMMISSION REGULATION (EU) 2020/878

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

New declared substances

diuron (ISO) (330-54-1)

octhilinone (ISO) (26530-20-1)

1,2-benzisothiazol-3(2H)-one (2634-33-5)

2-butoxyethanol (111-76-2)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9) Formaldehyde (50-00-0)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9) CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- · Hazard statements
- · Precautionary statements
- · Supplementary information

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

\*\* Changes with regards to the previous version

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific

legislation



# 026982 - ANTIGOTERAS MEMBRANA POLIURETANO Blanco

#### SECTION 16: OTHER INFORMATION \*\* (continued)

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### CLP Regulation (EC) No 1272/2008:

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled.

Acute Tox. 2: H330 - Fatal if inhaled.

Acute Tox. 3: H301 - Toxic if swallowed.

Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin.

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.

Acute Tox. 4: H302 - Harmful if swallowed.

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Carc. 1B: H350 - May cause cancer.

Carc. 2: H351 - Suspected of causing cancer.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Muta. 2: H341 - Suspected of causing genetic defects.

Skin Corr. 1: H314 - Causes severe skin burns and eye damage.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

#### Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

#### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LOgPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

#### \*\* Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal renders and its products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.