

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: 033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris

Other means of identification:

UFI: T9U0-S0H5-W00J-7PP2

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Decorative coatings for ferrous surfaces

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Productos JAFEP, S.L. Carretera de Barrax, s/n 02630 La Roda - Albacete - Spain

Phone: +34 967 44 05 96 - Fax: +34 967 44 26 12

jafep@jafep.com www.jafep.com

1.4 Emergency telephone number: +34 967 44 05 96 (9:00-14:00 ; 16:00-20:00)

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Flam. Liq. 3: Flammable liquids, Category 3, H226

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/face protection/protective clothing/protective footwear.

P370+P378: In case of fire: Use Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC) to extinguish.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains Neodecanoic acid, cobalt salt. May produce an allergic reaction.

UFI: T9U0-S0H5-W00J-7PP2

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

Date of compilation: 06/05/2011 Revised: 27/02/2024 Version: 9 (Replaced 8) **Page 1/13**

^{**} Changes with regards to the previous version

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

3.2 Mixture:

Chemical description: Miscellaneous products

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification	Chemical name/Classification		Concentration
CAS: EC:	Non-applicable 919-857-5	Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics(1)	Self-classified	
Index:	Non-applicable 01-2119463258-33- XXXX	Regulation 1272/2008 Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger	(!) (1)	9,9 - <19 %
CAS: EC:	Non-applicable 918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics(1)	Self-classified	
Index:	Non-applicable 01-2119457273-39- XXXX	Regulation 1272/2008 Asp. Tox. 1: H304; EUH066 - Danger	&	0,9 - <2,4 %
CAS: EC:	1305-78-8 215-138-9	Calcium oxide (as carbonate)(2)	Not classified	
Index:	Non-applicable 01-2119475325-36- XXXX	Regulation 1272/2008		0,29 - <0,9 %
CAS:	107-98-2	1-methoxy-2-propanol ⁽²⁾	ATP ATP01	
EC: Index: REACH:	203-539-1 603-064-00-3 01-2119457435-35- XXXX	Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	(1) (6)	0,09 - <0,24 %
CAS:	27253-31-2	Neodecanoic acid, cobalt salt(1)	Self-classified	
EC: Index: REACH:	248-373-0 Non-applicable 01-2119970733-31- XXXX	Regulation 1272/2008 Acute Tox. 4: H302; Aquatic Chronic 3: H412; Skin Sens. 1: H317; STOT RE 1: H3: Danger	72 - 🕦 🗞	0,09 - <0,24 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acut	Genus	
Neodecanoic acid, cobalt salt	LD50 oral	1098 mg/kg	Rat
CAS: 27253-31-2	LD50 dermal	Not relevant	
EC: 248-373-0	LC50 inhalation	Not relevant	

^{**} Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eve contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

⁽²⁾ Substance with a Union workplace exposure limit



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris



SECTION 4: FIRST AID MEASURES (continued)

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

It is recommended to avoid environmental spillage of both the product and its container.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris



SECTION 7: HANDLING AND STORAGE (continued)

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

5 °C Minimum Temp.: Maximum Temp.: 30 °C B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
Calcium oxide (as carbonate)	IOELV (8h)		1 mg/m ³
CAS: 1305-78-8 EC: 215-138-9	IOELV (STEL)		4 mg/m³
1-methoxy-2-propanol (1)	IOELV (8h)	100 ppm	375 mg/m ³
CAS: 107-98-2 EC: 203-539-1	IOELV (STEL)	150 ppm	568 mg/m ³

⁽¹⁾ Likely absorption through the skin

DNEL (Workers):

		Short e	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
Calcium oxide (as carbonate)	Oral	Not relevant	Not relevant	Not relevant	Not relevant	
CAS: 1305-78-8	Dermal	Not relevant	Not relevant	Not relevant	Not relevant	
EC: 215-138-9	Inhalation	Not relevant	4 mg/m³	Not relevant	1 mg/m³	
1-methoxy-2-propanol	Oral	Not relevant	Not relevant	Not relevant	Not relevant	
CAS: 107-98-2	Dermal	Not relevant	Not relevant	183 mg/kg	Not relevant	
EC: 203-539-1	Inhalation	553,5 mg/m ³	553,5 mg/m ³	369 mg/m ³	Not relevant	
Neodecanoic acid, cobalt salt	Oral	Not relevant	Not relevant	Not relevant	Not relevant	
CAS: 27253-31-2	Dermal	Not relevant	Not relevant	Not relevant	Not relevant	
EC: 248-373-0	Inhalation	Not relevant	Not relevant	Not relevant	0,2732 mg/m ³	

DNEL (General population):



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Calcium oxide (as carbonate)	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 1305-78-8	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 215-138-9	Inhalation	Not relevant	4 mg/m ³	Not relevant	1 mg/m³
1-methoxy-2-propanol	Oral	Not relevant	Not relevant	33 mg/kg	Not relevant
CAS: 107-98-2	Dermal	Not relevant	Not relevant	78 mg/kg	Not relevant
EC: 203-539-1	Inhalation	Not relevant	Not relevant	43,9 mg/m ³	Not relevant
Neodecanoic acid, cobalt salt	Oral	Not relevant	Not relevant	0,032 mg/kg	Not relevant
CAS: 27253-31-2	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 248-373-0	Inhalation	Not relevant	Not relevant	Not relevant	0,043 mg/m ³

PNEC:

Identification				
Calcium oxide (as carbonate)	STP	2,27 mg/L	Fresh water	0,37 mg/L
CAS: 1305-78-8	Soil	817,4 mg/kg	Marine water	0,24 mg/L
EC: 215-138-9	Intermittent	0,37 mg/L	Sediment (Fresh water)	Not relevant
	Oral	Not relevant	Sediment (Marine water)	Not relevant
1-methoxy-2-propanol	STP	100 mg/L	Fresh water	10 mg/L
CAS: 107-98-2	Soil	4,59 mg/kg	Marine water	1 mg/L
EC: 203-539-1	Intermittent	100 mg/L	Sediment (Fresh water)	52,3 mg/kg
	Oral	Not relevant	Sediment (Marine water)	5,2 mg/kg
Neodecanoic acid, cobalt salt	STP	0,37 mg/L	Fresh water	0,00062 mg/L
CAS: 27253-31-2	Soil	10,9 mg/kg	Marine water	0,00236 mg/L
EC: 248-373-0	Intermittent	Not relevant	Sediment (Fresh water)	53,8 mg/kg
	Oral	Not relevant	Sediment (Marine water)	69,8 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.11 mm)	CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CATII	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
*	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	**	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 19,41 % weight

V.O.C. density at 20 °C: 335,08 kg/m³ (335,08 g/L)

Average carbon number: 9,92

Average molecular weight: 140,42 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 335,12 kg/m³ (335,12 g/L)

EU limit for the product (Cat. A.I): 500 g/L (2010)
Components: Not relevant

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Odour:

Odour threshold:

Liquid

Viscous

Grey

Characteristic

Not relevant *

Volatility:

Boiling point at atmospheric pressure: 170 °C Vapour pressure at 20 °C: 262 Pa

Vapour pressure at 50 °C: 2029,13 Pa (2,03 kPa)

Evaporation rate at 20 °C: Not relevant *

Product description:

Density at 20 °C: ≈1726,3 kg/m³

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 06/05/2011 Revised: 27/02/2024 Version: 9 (Replaced 8) Page 6/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Relative density at 20 °C: ≈1,726

Dynamic viscosity at 20 °C:

Kinematic viscosity at 20 °C:

Kinematic viscosity at 40 °C:

Concentration:

Partition coefficient n-octanol/water 20 °C:

Not relevant *

Not relevant *

Not relevant *

Not relevant *

Solubility in water at 20 °C:

Not relevant *

Not relevant *

Decomposition temperature:

Not relevant *

Melting point/freezing point:

Not relevant *

Flammability:

Flash Point: >39 °C
Flammability (solid, gas): Not relevant *
Autoignition temperature: 265 °C
Lower flammability limit: Not available
Upper flammability limit: Not available

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Not relevant *

Oxidising properties:

Not relevant *

Corrosive to metals:

Not relevant *

Heat of combustion:

Aerosols-total percentage (by mass) of flammable

Not relevant *

Not relevant *

Aerosols-total percentage (by mass) of flammable components:

Surface tension at 20 °C:

Other safety characteristics:

Refraction index: Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

Not relevant *

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Date of compilation: 06/05/2011 Revised: 27/02/2024 Version: 9 (Replaced 8) **Page 7/13**



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris



SECTION 10: STABILITY AND REACTIVITY (continued)

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION **

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - IARC: Diiron trioxide (3); Hematite (Fe2O3) (3); Reaction mass of ethylbenzene and xylene (3); Hydrocarbons, C9, aromatics (3); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3); Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics (3); Neodecanoic acid, cobalt salt (2B)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

- CONTINUED ON NEXT PAGE -

Date of compilation: 06/05/2011 Revised: 27/02/2024 Version: 9 (Replaced 8) **Page 8/13**

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris

SECTION 11: TOXICOLOGICAL INFORMATION ** (continued)

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	А	Acute toxicity	
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics	LD50 oral	>5000 mg/kg	Rat
CAS: Non-applicable	LD50 dermal		
EC: 919-857-5	LC50 inhalation		
Neodecanoic acid, cobalt salt	LD50 oral	1098 mg/kg	Rat
CAS: 27253-31-2	LD50 dermal		
EC: 248-373-0	LC50 inhalation		

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION **

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus	
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1		20800 mg/L (96 h)	Pimephales promelas	Fish	
		23300 mg/L (48 h)	Daphnia magna	Crustacean	
		1000 mg/L (168 h)	Selenastrum capricornutum	Algae	
Neodecanoic acid, cobalt salt		>10 - 100 mg/L (96 h)		Fish	
CAS: 27253-31-2 EC: 248-373-0		>10 - 100 mg/L (48 h)		Crustacean	
		>10 - 100 mg/L (72 h)		Algae	

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics	BOD5	Not relevant	Concentration	Not relevant
CAS: Non-applicable	COD	Not relevant	Period	28 days
EC: 919-857-5	BOD5/COD	Not relevant	% Biodegradable	80 %
1-methoxy-2-propanol	BOD5	Not relevant	Concentration	100 mg/L
CAS: 107-98-2	COD	Not relevant	Period	28 days
EC: 203-539-1	BOD5/COD	Not relevant	% Biodegradable	90 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential		
1-methoxy-2-propanol	BCF	3	
CAS: 107-98-2	Pow Log	-0.44	
EC: 203-539-1	Potential	Low	

12.4 Mobility in soil:

Date of compilation: 06/05/2011 Revised: 27/02/2024 Version: 9 (Replaced 8) **Page 9/13**

^{**} Changes with regards to the previous version

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris



SECTION 12: ECOLOGICAL INFORMATION ** (continued)

Not available

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	le Description	Waste class (Regulation (EU) No 1357/2014)		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous		

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



14.1 UN number or ID number: UN1263
 14.2 UN proper shipping name: PAINT
 14.3 Transport hazard class(es): 3

 Labels: 3

 14.4 Packing group: III

14.4 Packing group: III

14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 163, 367, 650

Tunnel restriction code: D/E

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Maritime transport in bulk

according to IMO instruments:

Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

- CONTINUED ON NEXT PAGE -

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris



SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number or ID number: UN1263
 14.2 UN proper shipping name: PAINT
 14.3 Transport hazard class(es): 3
 Labels: 3

14.4 Packing group: III14.5 Marine pollutant: No

14.6 Special precautions for user

Special regulations: 223, 955, 163, 367

EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Not relevant **14.7 Maritime transport in bulk** Not relevant

according to IMO instruments:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



14.1 UN number or ID number: UN1263 **14.2 UN proper shipping name:** PAINT

14.3 Transport hazard class(es): 3 Labels: 3

14.4 Packing group: III **14.5** Environmental hazards: No

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Maritime transport in bulk Not relevant according to IMO instruments:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), octhilinone (ISO), 1,2-benzisothiazol-3 (2H)-one, 1,2-benzisothiazol-3(2H)-one.
- Article 95, REGULATION (EU) No 528/2012: Calcium oxide (as carbonate) (1305-78-8) PT: (2,3)
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- —tricks and jokes
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Laboral exposure to respirable crystalline silica must be controlled in accordance with Directive (EU) 2022/431, of the European Parliament and of the Council, of March 9, 2022, amending Directive 2004/37/EC, relating to the protection of workers against risks related to exposure to carcinogens or mutagens during work.

Specific provisions in terms of protecting people or the environment:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris



SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

· New declared substances

Neodecanoic acid, cobalt salt (27253-31-2)

· Removed substances

2-methylpropan-1-ol (78-83-1)

maleic anhydride (108-31-6)

Dipropylene Glycol Methyl Ether (34590-94-8)

Cobalt bis(2-ethylhexanoate) (136-52-7)

2-ethylhexanoic acid, zirconium salt (22464-99-9)

Hydrocarbons, C9, aromatics (128601-23-0)

Xylene (1330-20-7)

Masa de reacción de etilbenceno y M-Xileno y P-Xileno

Substances that contribute to the classification (SECTION 2):

· Removed substances

2-methylpropan-1-ol (78-83-1)

Cobalt bis(2-ethylhexanoate) (136-52-7)

Hydrocarbons, C9, aromatics (128601-23-0)

Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- · Pictograms
- · Hazard statements
- · Precautionary statements
- · Supplementary information
- · Substances contained in EUH208:
 - · New declared substances

Neodecanoic acid, cobalt salt (27253-31-2)

Removed substances

maleic anhydride (108-31-6)

Texts of the legislative phrases mentioned in section 2:

H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed.

Aguatic Chronic 3: H412 - Harmful to aguatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Flam, Liq. 3: H226 - Flammable liquid and vapour.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure. (Oral).

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

- CONTINUED ON NEXT PAGE -

Date of compilation: 06/05/2011 Revised: 27/02/2024 Version: 9 (Replaced 8) Page 12/13

^{**} Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

033810 - ESMALTE SINTETICO ANTIOXIDANTE OX EFECTO FORJA Gris



SECTION 16: OTHER INFORMATION ** (continued)

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer



The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

Date of compilation: 06/05/2011 Revised: 27/02/2024 Version: 9 (Replaced 8) Page 13/13

^{**} Changes with regards to the previous version